пр. Обуховской Обороны, д. 70, к. 2, Лит. А, Пом. 7-Н

Тел./факс: (812) 313 7363, www.rastro.ru

ИНН 7801012459, КПП 781101001, ОГРН 102 780 607 9960

p/c 40702 81087 20000 02042, K/c 30101 81020 00000 00704

Филиал ОПЕРУ ОАО Банк ВТБ в Санкт-Петербурге г.Санкт-Петербург

БИК 044030704, ОКПО 11149403, ОКОНХ 63100



(ANNEX III of the Regulation (EU) No. 305/2011) DECLARATION OF PERFORMANCE No. 1/2014

- 1. Unique identification code of the product-type: 5775-014-11149403-2010
- 2. Type, batch or serial number or any other element allowing identification of the construction product: (as required pursuant to Article 11(4)):

 Emulsified bitumous paste SLAVYANKA® Liquid Rubber coating protection against Ingress
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Surface protections systems of concrete
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer (as required pursuant to Article 11(5)): "Rastro", CJSC,
 70 Obukhovskoy Oborony prospect, bldg. 2, Lit. A Premises. 7-N, St. Petersburg, 192029, Russia
- 5. (Where applicable) Name and contact address of the authorised representative (whose mandate covers the tasks specified in Article 12(2)): not relevant
- 6. System or systems of assessment and verification of constancy of performance of the construction product (as set out in Annex V): system 2+according to EN 1504:2
- 7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: NB 1020 TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, S.P., POB. PRAHA, PROSECKÁ 76A, 190 00 PRAHA 9, ČR

performed

factory production control

under system 2+

and issued

certificate of conformity of the factory production № 1020-CPR-010030731

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
CO ₂ Carbon dioxide permeability	Sd > 50 m	EN 1504:2
Adhesion	≥0.8 MPa	EN 1504:2
Water steam permeability	class III (Sd > 50 m)	EN 1504:2
Water steam permeability rate	$W < 0.1 \text{ kg/(m}^2 \text{h}^{0.5})$	EN 1504:2
Ability to close cracks	class A5	EN 1504:2
Fire reaction	class E	EN 1504:2

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

General Director Vigovsky A.A. (name and function)

01.2014 (place and date of issue)

AAXTA® • CAARGHKA® • MXCDA® • AAXTA® • CAARGHKA® • MXCDA® • AAXTA® • CAA

(signature)

HO0 06